

PCT

WORLD INTELLECTUAL PROPERTY  
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER



(51) International Patent Classification<sup>6</sup> :

A61G 15/00

A1

(11) Int

WO 9604878A1

(43) International Publication Date: 22 February 1996 (22.02.96)

(21) International Application Number: PCT/US95/09681

(22) International Filing Date: 4 August 1995 (04.08.95)

(30) Priority Data:

08/289,372

12 August 1994 (12.08.94)

US

(71)(72) Applicants and Inventors: WALKER, Brock, M.  
[US/US]; 4095 Hullet Road, Okemos, MI 48864 (US).  
TIMM, Edward, E. [US/US]; 6860 North River Road,  
Freeland, MI 48623 (US).


(74) Agents: GOWDEY, Peter, W. et al.; Cushman, Darby & Cushman,  
9th floor, 1100 New York Avenue, N.W., Washington,  
DC 20005-3918 (US).

(81) Designated States: AU, BR, CA, CN, HU, JP, KR, MX, SG.

Published

With international search report.

(54) Title: SPINAL SUPPORT SYSTEM FOR SEATING



(57) Abstract

This invention is a spinal support device (10) for applying a directed and concentrated force on the sacrum to position the sacrum and pelvis to thereby establish a desired spinal posture when in a seated position. The device (10) provides isolatable force on the sacrum from the sacral base line downwardly to a bottom seat surface, and for a width across an individual's back approximately equal to twice the dimension of the posterior portion of the individual's sacrum.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LJ	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

## SPINAL SUPPORT SYSTEM FOR SEATING

Background of the InventionField of the Invention

The present invention relates to an improvement in a back support system that establishes a desired postural position by creating specific sacral pressure and to apparatus that will properly position the sacrum, the pelvis, including the iliac crests, and the supporting neuro-musculo-skeletal system to produce total pelvic stability.

Description of the Prior Art

Back pain, in concept and in fact, is not only prevalent in society but is an area of much research and patent activity. Back pain is something many individuals experience at work, at home, and during the trip therebetween. Back pain has many causes, but few cures. The latter is not for a want of trying. Rather, patents on a wide variety of back supports or support systems abound.

For example, the patents can be generally divided in groups including those relating to seat developments, sacral or lumbosacral braces, fixed cushions or supports, and inflatable devices.

The seat development area can be further subdivided into built-in supports, add-on supports, orthopedic seats, back rests, and office chair designs.

Prior to a summary review of these prior efforts, it should be understood that non-pathogenic back pain usually results from the presence of stress on the pressure on the neuro-musculo-skeletal system and affected interrelated anatomical structure. Sometimes that stress or pressure is generated internally within the spinal cord. In either case, the resulting stress can be due to inappropriately applied pressure or due to a distorted or damaged spinal column that has existed for varying periods of time, with resulting pain depending on the prior state of the spinal cord. Consequently, in many situations the neuro-musculo-skeletal system can be supported to either relieve or prevent development of unwanted and undesirable spinal pressure.

An early spine support device is described in Epstein, U.S. Patent No. 1,667,626. A wooden frame is used to mount a series of spring bands that form a curved face. A batting material fills the space between vertical braces and the whole device was covered with fabric. Using adjustable hooks the device was adjustable to accommodate different sized persons. The device has a width about equal to a person's back and is shown being positioned in the lumbar region to provide uniform support over a broad region.

The built-in devices are exemplified by Sopko, Jr. U.S. Patent No. 3,145,054 and Burton, U.S. Patent No. 3,501,197. Sopko relates to a portable chair that incorporates a contoured pneumatic cushion which applies pressure to the posterior surface, in the sacroiliac area, and varies the pressure by forward and rearward

movement of the occupant against the back supporting pneumatic cushion.

Burton attempts to restrict the body's movement into the back/seat junction area, where the ischial tuberosities of the pelvic girdle wedges into this back/seat area, by incorporating a rigid back/seat element into the seat to prevent such wedging.

The add-on devices include a variety of devices as shown in U.S. Patent Nos. Weinreich 4,753,478; Quinton et al. 4,718,724; Baxter et al. 4,516,568; Scott 4,634,176; and Pasquarelli 2,831,533.

Each of these devices includes a portion that extends across the entire back of the person as seated in the seat. In Weinreich the support is in the form of a pair of tubular cushions. Quinton et al. suggest that it had proved difficult to standardize the location of lumbar support cushions and thus developed a vertically adjustable lumbar support cushion. Baxter et al. disclose a multi-compartment air bladder, including side and center sections, so that air pressure can be applied on selected lumbar and sacroiliac areas of the body. Scott is also a vertically movable back support but has a greater area than that to Quinton et al. Pasquarelli discloses use of a dorso-lumbar curve support in the form of an elongated cushion that applied pressure across the full width of the person's back.

The lumbosacral braces include Rowe, U.S. Patent No. 4,930,499; Brooks et al., U.S. Patent No. 4,475,543; Hyman et al, U.S. Patent No. 4,576,154; Carabelli, U.S. Patent No. Des. 296,930; and Lampert, U.S. Patent No. 2,554,337.

Several patents disclose use of a fixed cushion. These include Parrish, U.S. Patent No. 4,876,755; Snyder et al, U.S. Patent No. 4,522,447; and the Meares design patent, U.S. Patent No. Des. 277,316. The cushion used by Parrish is shaped as a capital "I" and supports the cervical, thoracic and lumbar regions. Snyder et al. designed foam cushions with segments having varying degrees of elasticity to provide inversely proportional support for both seating and backrest surfaces with the softest material provided where pressure would be highest.

Meares shows a design for an orthopedic device that provides full sacral pressures. The design patent does not explain how this device works or functions. However, an associated instruction book explains that the device is to be used by a person primarily in a horizontal condition. The device, while constructed from rubber in soft foam rubber, has a hollow interior and the edges are stiffer due to the presence of sidewalls that surround the hollow interior. Thus, the resistance provided by the Meares device is not uniform. The center is softer than the peripheral edges.

To use the device while lying on the floor, the device is placed on the floor and the user then rolls over onto the device. The instructions explain that the device has a wide end and a narrow end with the wide end being positioned so that it points toward the head. When one first gets on the device, the knees are to be bent and the tail bone is to be rocked down toward the floor. This movement is claimed to help position the curve of the sacrum (tailbone)

into the curvature or cradle formed in the device.

As shown in the design patent, the device includes two raised portions on the anterior surface and a flat rear or posterior surface. Because the device is molded from soft rubber, and has a hollow interior, a wider cradle area is formed between the two raised areas.

The Meares device is about 7.25 inches long and has a width of 2.75 inches at the top and about 1 inch at the bottom. The upper raised area extends for about 2 inches, the cradle area then extends for another 3.25 inches with the lower raised portion extending for about .75 inches. Thereafter the device slopes toward the narrow end. The device should be used on a firm surface and the instructions suggest that a book could be used if the person was bedridden or a piece of plywood could be positioned under the hips to provide the feeling of a firm support.

The Meares instruction materials also state that his device can be used in a car, truck or a straight back chair. To use the Meares device in such a situation the rubber device is bent into a curved shape and then it is placed both under and slightly behind the person. The instructions also state the seat cushion is soft, a bendable book could be inserted under the rubber device to increase lift. The bent member should cradle the sacrum as when the device was used on the floor.

Thus, Meares suggests, indeed requires, full sacral pressure that is not adjustable with respect to the intensity of pressure being applied. Meares preference is to create constant pressure while the user is in a supine position.

It is also important to note that Meares isolates pressure along the full length of the sacrum. This is intended to provide a treatment to an injured set of muscles, with the piriformis and psoas muscles being of primary concern. Meares' desire is to literally move the whole of the sacrum upwardly (when lying down - movement is toward one's front). If the sacrum can be moved that way, and the hips are allowed to move in the opposite direction, that is, in a sense, to fall downwardly over the sides of his device, both the piriformis and psoas muscles will be stretched to relieve muscle spasms.

#### Summary of the Invention

To gain an appropriate understanding of the utility and effect of the present invention, it is important to first understand the skeletal features of a human body, as well as how such features interact and affect one another. In that regard, reference will be made to the entire neuro-musculo-skeletal system of the human anatomy, as well as the interaction between those anatomical systems.

In a normal person, the spine, when viewed from the front, preferably will form a relatively straight vertical line. The function of the spine is in part mechanical, since it supports the body from the waist up, and in part protective, since it protects and houses the central nervous system or spinal cord. The spine is comprised of seven cervical vertebrae, twelve thoracic vertebrae and five lumbar vertebrae. Below the lumbar vertebrae is the sacrum and below that the bones that form the coccyx. The



upper one third of the sacrum is an area identified as the sacral base.

5 The cervical or upper portion of the spine generally curves forward as a smooth and flexible "C" shaped element which supports the head and a percentage of body weight. This upper portion, because of its high flexibility, allows for rotational movement as well as fore and aft movement.

10 The thoracic portion of the spine, sometimes referred to as the middle back, will curve in the opposite direction, that is, rearwardly and then forwardly again. The thoracic portion supports the rib cage and the upper body portion above that area. Because the ribs are connected to the  
15 thoracic portion of the spine, the ribs themselves prevent the thoracic spine region from being as flexible as the cervical portion, and in fact, make the thoracic portion relatively rigid.

20 The next portion of the spine, the lumbar region or lower back, again curves in the opposite direction from the curvature of the thoracic portion. The sacral and coccyx portions extends therebelow and again curves forwardly.  
25 The lower back portion is supports the major portion of the upper body and, consequently, is under more compressive stress than the remaining portions of the spine.

30 The most normal curves of the spine are developed when the human body is standing in an upright manner and exhibiting good posture. As the body undergoes changes when getting into a seat and when seated, especially if one is to perform functions while in a seated position, the  
35 normal curvature of the spine is generally distorted. This is due to the fact that many, if

not most, chairs do not give good spinal support. Consequently, backaches or stresses develop during sitting, especially during extended periods of sitting. Such extended sitting can create aches, soreness and disfunction.

This is true for the common man as well as in specialized instances, such as when race drivers must remain seated in the one position for hours at a stretch.

Thus, one of the principal objectives of the present invention is to support the lumbar lordosis of the spine in a shape similar to the shape found in a normal standing posture, and to provide this support when the individual is seated. One objective of the present invention is to support, principally, the sacral base. The goal is to prevent muscles from spasming by providing support and thus reducing the likelihood of muscle fatigue.

In Bridger, U.S. Patent No. 3,740,096, there was a recognition that abnormal strains of the spine can be reduced if the occupants weight is distributed throughout each disc and vertebrae in the spine evenly so that a mechanical balance is created between the related antagonistic muscle groups and ligaments. While Murrow, U.S. Patent No. 4,489,982 and Dunn, U.S. Patent No. 5,114,209, recognized the importance of correct posture when sitting, they suggested use of full width back or lumbar supports. Neither recognized the importance, or even the desirability, of localized pressure, especially to the sacral base region.

The discs within the spine, separating the vertebrae, are under minimal mechanical load when bearing only compressive stresses resulting from

the body's weight. However, when the spine is flexed from its normal curvature, such as when standing erect with good posture, the discs then must bear additional compressive and/or tensile stresses due to forces applied by the muscles and ligaments in order to maintain the mechanical equilibrium when the spine is in a new flexed position. It should be noted that the payload on the neuro-muscular-skeletal (NMS) system is vastly different between sitting and lying down positions.

A great deal of spinal pain can be traced to excessive stresses applied to these discs and to the vertebral complex and the interrelated neuro-musculo-skeletal system. Consequently, developing an improved seating approach requires that one minimize neuro-musculo-skeletal stresses when the individual is in a sitting posture. When this is achieved, it will provide superior comfort and endurance to the occupant of a seat and provide significant benefit during extended sitting periods.

Many people must perform some function when in a seated position. If this were not the case then the goal of minimizing stresses on vertebral complex could be accomplished relatively simply by inclining the back portion of the seat away from the vertical position to more closely approximate spinal curvature positions when the person was erect. However, tasks must be performed while seated. This necessarily requires upper body motion. As such motion occurs, it will create varying degrees of stress throughout the neuro-musculo-skeletal system. This is caused by the movement of muscles and ligaments associated with the body motion as

movement occurs when the body changes position. Related stresses can also be aggravated by movement, especially when compared with stresses found in a perfectly static seated posture.

5 Motion moves the upper body from its center of gravity, or from an equilibrium position established by the vertebrae, muscles and ligaments holding each vertebrae in the system change position and move in response. As the  
10 center of gravity changes, and the equilibrium position changes, this also increases bending moments around each vertebrae and thus discs are placed under additional, though varying, stresses.

15 When seated the major portion of the upper body, and certainly its center of gravity, is positioned above the fixed end of the spine. When bending of the spine takes it out of its columnar position, and thus out of equilibrium,  
20 motion occurs about a joint between the fifth lumbar vertebrae and the sacrum. Consequently, one objective of the present invention to stabilize and correctly orient this lumbo-sacral joint. This is important in providing a  
25 functionally active and comfortable seated position where the sacral base is supported. In that condition sitting can be endured for sustained periods. More specifically, if a seating device is arranged so that the sacrum,  
30 and in particular the sacral base, is not securely positioned at an angle that allows the spine to support the weight born by the fifth lumbar vertebrae, without requiring additional bending and shear stresses to maintain  
35 equilibrium of the spine, then no amount of additional support of the occupant's upper body

will result in an optimally functional seat. It will also not provide sitting comfort for an extended time.

5 The present invention relates to a method and apparatus for supporting the lumbar lordoses of the spine to achieve a spinal shape similar to the shape found in a normal standing posture, but while seated. This is accomplished, in part, by securely locating a seated person's pelvis in a position that will maintain good spinal posture while seated. First, the sacrum itself must be properly positioned by locating the sacrum along its posterior surface. This is done by applying pressure directly over the posterior surface of the sacrum, and principally to the upper one  
10 third of the sacrum, the sacral base. Secondly, the force generated by such a sacral pressure exerting device must be resisted through a combination of frictional, gravitational or other mechanical means in order to prevent movement of the person in an anterior direction across the surface of the seat or away from the sacral support and away from the supporting force.  
15

20 The sacral support of the present invention is designed to position the sacrum but to do so in a way that permits the ability to also compress adjacent soft tissue in a variable manner. The present invention permits the option to adjust the specific pressure to the sacral base and to change the pressures per square inch at that region. Thus, it is possible to vary the intensity of the specifically applied pressure to the sacral base to thereby achieve the support of and/or movement of the sacrum in a posterior to an anterior direction: This pressure can be  
25  
30  
35 directed against the individual at an angle that

can vary from, for example, 15-20 degrees, plus and minus from a direction perpendicular to the sacrum. The most effective direction or angle will depend upon a number of factors, such as, for example, the shape of the seat, the angle of the seat back relative to the seat bottom, and the size of the person. However, the present invention can provide the desired sacral support, in a sitting condition, regardless of what position the seat is adjusted to with regard to its angle of incline.

Support of the seated individual is important since the payload on the neuromuscular-skeletal system is quite different between sitting and supine positions. That payload difference also dictates muscle function without substantially compressing the adjacent soft body tissue in order to maintain a desirable sacrum base angle. The posterior surface of the sacrum is a relatively flat surface and is covered only with a minimum amount of soft tissue and muscle. Thus, it is amenable to be oriented by placing it in close proximity to an orienting surface. This orienting surface will preferably maintain a desirable sacral base angle of from about 20° to 50° from the plane of a substantially horizontal seat, but corrected for inclination of the spinal column from vertical, or for back rest inclination.

Other objects, features, and characteristics of the present invention will become apparent upon consideration of the following description in the appended claims with reference to the accompanying drawings, all of which form a part of the specification, and wherein referenced

numerals designate corresponding parts in the various figures.

Brief Description of the Drawings

5           FIG. 1 is a cross-sectional view of the present invention with reference to a seat bottom and seat back, the lumbar vertebrae and the sacrum;

10           FIG. 2 is a front elevational view of the present invention;

          FIG. 3 is a side view of the rigid sacral support;

          FIG. 4 is a cross-sectional view of a modified form of the present invention;

15           FIG. 5 is an exploded perspective view of the embodiment of the present invention shown in Fig. 4;

          FIG. 6 is a cross-sectional view of another embodiment of the present invention;

20           FIG. 7 is a cross-sectional view taken along line 7-7 in Fig. 6;

          FIG. 8 is a front view of another embodiment of the present invention;

25           FIG. 9 is a side elevational view thereof as positioned in a seat relative to an individual;

          FIG. 10 is a top plan view thereof;

          FIG. 11 is a front elevational view with the sacral support block removed; and

30           FIG. 12 is a vertical, partial cross-section through the support block.

Detailed Description of the Present Invention

35           With reference to Fig. 1, one embodiment of the present invention is shown in cross-section, and generally indicated at 10. The device 10 is shown being used between a bottom seat 12 and a

seat back 14, with only portions of the seat structure being shown.

5 In order to correlate the present invention and its effect on the anatomical components of a person's body, Fig. 1 includes the pelvis 16, the five lumbar vertebrae, generally indicated at 18, with the vertebrae specifically referenced as L1-L5, respectively. A first and lowermost thoracic vertebrae is shown at 20. The sacrum is shown at 10 22 and the upper one third is the region or area called the sacral base. Below sacrum 22 is the coccyx 24, which is comprised of a series of smaller bones that, as a group, tend to curve in an anterior direction. In older adults the 15 smaller coccyx bones can actually fuse together and are considered to be a part of the sacrum.

As noted, the sacrum 22 includes a sacral base or baseline at the top one third of the sacrum, indicated at 26, and a sacral apex at the 20 bottom thereof, indicated at 28.

The present invention can include a base structure, generally indicated at 30, comprised of a vertically extending back brace 32, a bottom member or bracket 34. The bottom member, as 25 shown in Fig. 1, can be inserted between the seat back 14 and seat bottom 12 thereby supporting and positioning the invention relative to the seat. As will be pointed out hereafter, this bottom member can have various forms depending upon the 30 configuration of the support device, the seat, or it could be built into a seat. The back 32 is preferably connected to the bottom member 34 by a hinge 40 that includes hinge extensions 36 and 38. This hinge structure can be attached to the 35 back and bottom members by any convenient means, such as glue, epoxy, bolts or screws.



The present invention principally includes a block member 44. Block member 44 provides the support and ability to place localized force or pressure on the sacrum, and most directly on the sacral base. Block 44 is preferably comprised of a rigid material and is shown in greater detail in Figs. 2 and 3.

It should be understood that this rigid support block 44 can be used by itself, with or without a cover and with or without the base described above. Block 44 could also include, or be provided with, various additional members attached to it, either removably or permanently. For example, attached to its anterior or front face could be a form of padding, or a hydraulic bladder, as shown in Fig.1 at 46, or a combination thereof. The padding could be comprised of a textile material, either woven or knitted, a non-woven material, batting, a foam layer, a gel filled bladder or other man-made or synthetic padding or body conforming materials. The goal is to provide an area of localized force but to simultaneously minimize the developed of points of contact. The preferred effect from the use of block 44 is to provide sufficient force or pressure on the sacrum, without substantial compression of adjacent soft tissue, and to develop the desired control over pelvic rotation. The padding or surface material on block 44 will also aid in isolating out or damping vibration to the sacrum.

In situations when block 44 is to be used by itself, a rearwardly extending seat support or engagement flap, preferably flexible, could be provided as described in more detail hereafter. This flap would slide between the seat lock and

bottom cushions to allow proper placement of the block on the seat and to hold the block in place.

Block 44 should itself preferably be stiff enough so that it will not bend or flex, easily or substantially, nor be easily moved from its predetermined position in the seat. It can be constructed, fabricated or molded from a variety of materials including plastic, reinforced plastic, rigid foam, metal or other similar materials. Further, this invention is intended to encompass use of a curved member that will, in use against the posterior of an individual, flatten or conform to the shape of the sacrum under a 1-4 psi load.

Where a hydraulic bladder is used as the padding 46, it is preferably filled with an inert liquid, having a viscosity varying from about 0.01 to about 10,000 poise at 20 °C. Such material may include flowable gels or thixotropic gels. Also, the bladder could be pneumatic and employ a fixed or variable volume of air or other inert gas. Where a variable volume of gas is desired, use of a conventional pneumatic pump, either hand operated or as part of an automatic system, could be used. Because these are conventional, further description is not believed required.

The desirability from using such bladder or members is to provide both a degree of protection for the individual, prevent development of point forces and to dampen the effect of any shocks during use. Also, use of the volume adjustable bladders allows the intensity of the force provided by block 44 to be adjusted.

As another alternative, the rigid block could have its anterior or front face covered

with "CONFOR" foam, a type of material that is designed to conform to shapes placed against it. The bladder could also be filled with water or a gel that would protect the soft tissue and dampen movement and vibrations.

Positioned above the rigid sacral support block 44, and the padding 46, is an additional support member 48, which has a generally U-shaped form as shown in Fig. 2. The surrounding support 48 can be a fluid filled bladder or foam and is preferably designed to provide lumbar and muscle support specifically for the supra-pelvic muscles and para-vertebrae muscles. However, the area of support 48, which can be about 100 square inches but can vary from 20 in<sup>2</sup> to 200 in<sup>2</sup>, preferably provides less anterior pressure than does block 44. For example, the support 48 could be about 10 inches high and 12 inches wide but its dimensions could vary from about 5 to about 20 inches in height and from about 6 to about 24 inches in width. The ratio of anterior pressures applied by block 44 relative to support 48 will be preferably about 2:1, but could vary from about a 1.1:1 ratio to about a 10:1 ratio.

The amount of anterior force preferably exerted by the whole assembly to the sacrum, and primarily the sacral base, will range from about 20-40 pounds in a seat belt type car seat environment. The applied force in an office chair configuration will be about 10 pounds since only friction and gravity can resist the application of anterior forces. These forces could also range from 10 to 50 pounds in a car seat environment and from about 5 to about 25 pounds in a fixed or office type chair.

A cover 50 can be provided over the rigid sacral support 44 and the padding 46. A cover 52 could also be provided on the exterior of the support 48. It would also be possible to have one cover extend over the whole assembly. Such a cover could be loose or a shrink-wrap type conforming cover.

While the device as shown in Fig. 1 is a separate unit that can be easily placed into position by sliding the bottom bracket 34 in between the seat back and the seat bottom, with similar easy removal of the device 10, this structure could also be built into the seat back 14. In that case, the covers 50 and 52 would be replaced by the main cover for such a seat.

As shown in Fig. 3, the rigid sacral support block 44 includes a rear surface 54, a top surface 56, and a front or anterior surface generally indicated at 58. That front surface 58 includes both a sloped or slightly curved upper portion 60 and an enlarged or bulbous portion 62 adjacent the bottom or in the lower portion of block. This latter enlarged portion extends anteriorly or forwardly beyond the upper portion 60. The surface below portion 62 is also sloped rearwardly to form a bottom surface 64. What is important is that the front or anterior surface 58 provide specific pressure contact, along a relatively narrow side-to-side path along the spine, in the area of the sacrum and specifically along the posterior surface thereof so that localized force is applied to the sacrum, and in a most preferred embodiment proportionally greater force will be applied to the sacral base portion of the sacrum. If the anterior surface 58 has a sufficient elongated curvature the

bulbous portion could be subsumed, in a more gradual curve, within the overall curvature of that surface still extending outwardly at the bottom so that the whole sacrum will be supported yet supporting forces will still be concentrated on the sacral base. As the upper portion 60 of front surface 58 is more of a ramp or slope, then the desired lower sacral pressure will come from the bulbous portion 62.

As can be seen by comparing Figs. 1 and 3, the front face 58 has a shape that will generally conform with or mimic the shape of the posterior shape of the sacrum.

The sacral support block 44 is designed, as a rigid structure, to localize the placement of pressure, or the desired supporting and corrective force, directly on the sacrum. In the most preferred embodiment, this force is concentrated on the upper one third of the sacrum, the sacral base. In each of the various embodiments, however, the sacral support block 44 is designed to apply force in a way that concentrates specific pressure or forces on and along the sacrum, that is along a narrow path relative to other parts of the back or posterior, specifically relative to the tissues adjacent the spinal column.

When block 44 is used by itself, the block 44 can also include a flexible, rearwardly extending tether, shown in dotted line at 66. Such a tether allows the block to be used by itself, without the additional bladder 48, and to be positively positioned and held in a seat or chair. The block and tether 66 are easily positionable so that an individual can place block 44 at the point it is needed and tether 66,

by sliding between the seat and back, will hold it in that position. Tether 66 can be made of any flexible material, preferably plastic, but a textile material, such as a stiff length of woven or knitted synthetic yarn, could be used as well. Also, tether 66 could be molded integrally together with block 44 or, alternatively, tether 66 could be separately constructed and then attached to block 44 by any convenient method.

As referenced previously in some embodiments the sacral support block 44 works in conjunction with an outlying bladder 48 so that parts of the individual's back, adjacent the sacrum, can be supported in specific relationship to the support provided by and the force being applied by the sacral block. When the fluid volume of bladder 48 is adjustable, the force applied by block 44 can be adjusted. This, in turn, will develop the appropriate positioning of the pelvis and the lower portion of the spine to best minimize compressive, bending and shear forces in the spine when seated.

The sacral support block 44 does not extend across a large portion of the width of an individual's back. Similarly, it does not extend across a large portion of a seat back. Rather, it concentrates the application of pressure or force along a relatively narrow band and thus isolates the application of the desired force and support to a relatively narrow area. While not essential, it is preferred that the sacral support block 44 have a shape that is larger across its width at the top and narrower at the bottom. This produces a block having a generally inverted triangular shape.

5 The dimensions of the rigid sacral support 44 can be, for example, approximately 2 1/2 inches in width across the top surface 56, as seen in Fig. 2, with approximately a width of the bottom 64 of about 1 inch. The overall height, from the bottom surface 64 to the top 56, can be, for example, about 5 inches.

10 With reference to Fig. 3, the front to back thickness across the top surface 56 from the rear surface 54 to the front sloped surface or ramp 60 is about 0.75 inch, whereas the forwardmost portion of the enlarged area 62 from rear surface 54 is about 1.5 inch.

15 The size ranges for the sacral support block 44 will vary according to an individual's height, with the following table showing roughly the dimensions for a small adult frame weighing about 150 lbs, a normal adult size frame weighing about 150-190 lbs and a relatively large adult frame  
20 weighing more than about 190 lbs.

22

	<u>Small</u>	<u>Normal</u>	
<u>Large</u>			
Height	3.5	5.0	6.5
Top Width	1.7	2.5	3.25
5 Bottom Width	0.7	1.0	1.3
Top Thickness	0.5	7.5	0.75
Bottom Thickness	1.0	1.5	2.0

10 For this rigid sacral support block the top to bottom width ratio is about 2.5:1 but could range from 1.5:1 to about 3:1. Likewise, the top to bottom thickness ratio is inverse to the width and is preferably about 1:2 but could range  
15 between 1:1 and 3:1 depending on the inclination of the device from vertical.

However, the top width of this distance could vary from 3 times the width of the sacrum at the sacral base to a dimension approximately equal to the width of the posterior portion of  
20 the sacrum still at the level of the sacral base and decrease progressively to the bottom of the block where the width is greater than or equal to the width of the sacrum at that point.

As noted previously, the front surface 58 includes the sloped or curved portion 60 and a bulbous portion 62 or an elongated curvature, such as, for example, is shown in Fig. 6. Fig. 1 shows that the top surface 56, when block 44 is positioned on a seat in its preferred location and an individual is seated back in the seat, will be located approximately at a level with the sacral base line 26. Block 44 will extend  
30 downwardly from that point to the top of bottom seat 12 and the anterior surface 58 curves or extends forwardly in a progressive manner from  
35 top to bottom. This provides continuous and



increasingly forwardly directed pressure on the sacrum which is itself curving forward away from the rear seat 14.

5 The block 44 is designed to preferably extend horizontally adjacent the sacral base line 26, a distance approximately equal to twice the width of the posterior portion of the sacrum. This is shown, for example, in Fig. 7. However, this horizontal distance could vary from 30% to 10 300% of the width of the posterior portion of the sacrum, measured at the sacral base, and decrease progressively to the bottom of the block where the width is about 30 % to 300 % of the sacrum width at the bottom of block 44.

15 We have found that when using a rigid sacral support 44 of the type just described fitted in an office chair, the support device will produce sacral pressures in the range of 1 to 2 psi, and that those pressures provide suitable pelvic 20 stabilization. In most office chair configurations, only the combined mechanisms of friction and gravity will hold an individual back against the support block. Thus, forces greater than 1 to 2 psi will generally not be obtainable.

25 When the device according to the present invention is fitted in an automobile seat, however, where friction and gravity are aided by the additional presence of a seat belt, sacral pressures in the range of 2 to 4 psi can be 30 generated with a corresponding greater degree of pelvic stabilization. Such pressures have been measured where the individual was seated in a static position. When an individual would be operating pedals, or move or be braced during 35 cornering, those pressures will vary and can

increase to 10 psi or more, depending upon the amount of exertion and vehicle speeds.

5 Air bladder 48 will generally be inflated to a pressure less than about 50% of the pressure exerted by the sacral pressure block 44. We have found that when the air bladder 48 is inflated to a pressure greater than about 50% of the pressure indicated on a sacral pressure gage for testing the amount of pressure exerted by the rigid support block 44, the sacral pressure loses its effectiveness in providing pelvis stabilization. For example, with an initial sacral pressure of 2 psi when seated, inflation of the air bladder 48 to 0.3 psi relieved the value of the sacral pressure applied by block 44 to downwardly to a value of 1.2 psi. This lower pressure still provided effective pelvic stabilization. However, when the air bladder was further inflated to 0.5 psi, the sacral pressure fell below 1 psi and pelvic support was no longer adequate.

10 Fig. 4 shows a second embodiment of the present invention. This embodiment continues to show use with a car seat having a bottom seat 12 and a back seat 14. The pelvis is shown at 16, the sacrum at 22, the lumbar vertebrae at 18 while the thoracic vertebrae are generally indicated at 20.

15 In this embodiment, the device is generally indicated at 80 and includes a back support 82, an upper or exterior support 84 and a rigid support block 86. The rigid support block 86 can also be provided with a cover 88, although the latter is not essential. This cover can be either in the form of padding, a hydraulic bladder or a combination of those elements. As

shown in Fig. 4 the cover 88 is a fixed volume, fluid filled bladder.

5 In this embodiment, the back support 82 is preferably a molded, one piece structure that is generally L-shaped, a perspective view of which is shown in Fig. 5. The back support 82 can include a vertical upright portion 90 and a rearwardly extending portion or tether 92. As shown, the back support 82 is formed as an  
10 integral one piece unit and can be constructed of a variety of materials, including plastics, semi-rigid or rigid foams or even metal. It is preferred, however, that the rearwardly extending portion 92 have some flexibility so that it can  
15 accommodate various shapes and curvatures that may exist between bottom and rear seats.

Fig. 5 also shows, in an exploded fashion, the upper and side support member 84, as well as the rigid support block 86.

20 The support 84 will again have a generally U-shaped form with an upper portion 94 and two side portions, 96, 98.

Cover 88 or block 86 could also be formed directly from the foam material used to produce the support 84. Such a cover could simply be an  
25 additional front surface left spanning across the interior side of opening 100 with the bottom of that cover structure being shown by dotted line 101 in Fig. 5. Alternatively, cover 88 could be  
30 a padded textile material or, as with prior embodiment, a variety of other materials or combinations thereof.

Block 86 preferably has a shape and configuration similar to that previously  
35 discussed with respect to block 44. Here again,

it is preferred that the block 86 be molded from plastic formed from another rigid material.

In use, the block 86 could be used with a reduced or smaller version of the support 82, or by itself, or it could be used in a combined fashion, as shown in Fig. 4, with the back support and the upper support 84. In the latter case the separate elements would operate collectively as a back and lumbar support assembly.

The foam used to produce support 84 would be of a resiliency or density suitable to provide some additional support for the individual in a lumbar area, but not so much a support that the specific pressure sought to be provided by block 86 was either relieved or not. For example, the foam used for member 84 could be polyurethane, EVA or foam rubber. Where foam is used a foam density preferably of about 2 to about 20 pound per cubic foot is preferred.

The size and dimensions of block 86 remain similar to those described above for block 44.

It should also be understood that the whole assembly 80 could be formed as an integral unit, and molded with varying densities of plastics or foams. This would result in a one piece structure that could be conveniently used by an individual, and even carried from one seating environment to another. In that way, the device could first be used in an automobile while travelling to and from work, and then carried into the office and next used in that individual's office chair environment to provide additional sacral support during the work day. After work, the device would again be used in the car for the trip home.

Another embodiment of the present invention is shown in Figs. 6 and 7, and could be a modified version of either prior embodiment as shown in Figs. 1-3 or Figs. 4-5, respectively. The base support as shown, for example, could be the back support, generally indicated at 30.

The device that is shown being used with respect to the bottom seat 12 and the back seat 14 is the device generally indicated at 10 which includes a base member, generally indicated at 30, an air bladder 48, a rigid sacral support lock 44 with a hydraulic bladder 46 provided thereover. The difference between this and the Fig. 1 embodiment is the use of side bolsters 110 and 112. Bolster 112 is shown in dotted line in Fig. 6 and both are shown in the Fig. 7 top plan view. Bolsters 110 and 112 are pivotally connected as of 111 to the back brace 32 so that each bolster can pivot outwardly away from the individual, as shown by the arrows adjacent the pivot connections 111. This pivot 111 connection can be by hinge or other convenient mechanism (not shown in detail), the only requirement being that bolsters 110 and 112 be pivotable toward and away from an individual sitting on seat 12.

As shown in Fig. 7, each bolster can include an upward, inwardly curving portion shown at 114 and 116, respectively. These inwardly curving portions are designed so that they will come up over the hips of the seated individual, as shown in Fig. 7, and also allows them to extend over the iliac crests, shown at 118 and 120. The front portions of the side bolsters 110 and 112 are connected together by means of a lap belt 122 and a suitable buckle 124 which will permit the belt to be snugly tightened around the

individual. This combined belt and bolster assembly will tend to apply pressure in the direction shown by the arrow A in Fig. 6. Belt 122, together with the bolsters 110 and 112, will capture the iliac crests of the seated individual and will thereby prevent movement of the pelvis.

This support system can also be used in a race type vehicle, which has a three to five point restraint system, to accommodate higher G force requirements. In this situation, the support elements could be customized for an individual driver and constitute part of an integrated, customized seat and support structure. The function and operation of the elements would be the same, however, the conditions, reactions and forces would simply be more severe.

Figures 9 through 12 show an additional embodiment of the present invention and one that is mechanically adjustable.

As shown in Figure 8, the support apparatus, generally indicated at 130, is comprised of an outer frame 132 in which two pivotally mounted threaded rods, 134 and 136 respectively, are pivotally mounted. A rod drive assembly, generally indicated at 138, is provided to rotate rods 134 and 136. This operation will be described further below.

A face plate 140 is connected to each of rods 134 and 136 by suitable threaded bearings, one of which is shown in phantom at 142. This permits face plate 140 to traverse vertically within frame 132. A sacral support block 144 is connected to face plate 140 by means of upper and lower supports 146, 148, respectively, which, as shown in Figure 12, are connected to block 144 by

pin connections 150. The pin connections 150 permit the ends of each support 146 and 148 to pivot and thus move relative to the sacral support block 144.

5 Supports 146, 148 each extend rearwardly, through face plate 140, within frame 132, and into a suitable block drive assembly, generally indicated at 152. The upper and lower supports 146 and 148 can either comprise threaded rods, at  
10 least the interior end of which is threaded, or, alternatively, they can comprise piston rods. What is required is a way to permit block 144 to be manipulated or moved. The block drive assembly 152 is provided to move the block  
15 supports 146 and 148, either uniformly or unilaterally, inwardly and/or outwardly relative to frame 132. In this way, the sacral support block 144, or its upper or lower portion, can be moved toward and away from frame 132 and thus, as  
20 shown in Figure 9, toward and away from an individual in a seat. Because block supports 146 and 148 can move independently of one another, it is possible to cause block 144 to articulate in a way designed to best provide support for an  
25 individual. Consequently, the top or the bottom of block 144 can be positioned so that the block itself can be located at varying angular positions, relative to each other and relative to the plane established by face plate 140 or the  
30 seat back 14'. Thus, block 144 can be positioned differently from the position as shown in Figure 9.

The sacral support block drive system 152 can be comprised of one or more electric motors  
35 154, which in turn drive suitable gear assemblies to cause the upper and lower block supports 146,

148 to move inwardly or outwardly, as shown by the double arrows in Figure 12. Such a gear assembly is generally indicated at 156 in Figure 11, and can include suitable gearing so that when operatively connected to drive motor 154 the block supports will be moved in a desired direction. This drive system could also be controlled in a way similar to the way car seats with finger controls can be moved, or via a memory system. These are now conventional and further description is not necessary.

Drive assembly 138 also includes an electric motor 158, as well as a suitable worm gear drive 160 that will connect directly to the tops of rods 134 and 136 and cause them to operate in a clockwise or counterclockwise direction.

The sacral support block 144 can be a rigid member or, alternatively, as shown in Figure 12, could include a hydraulic bladder 170, located along the upper one-third of the support, with the lower two-thirds being covered by a foam pad 172. For aesthetics, a fabric cover 174 could extend over both the bladder 170 and the foam pad 172. In this configuration, the hydraulic bladder 170 is relatively incompressible whereas the foam portion, in the lower two-thirds, is compressible. It should also be understood that the hydraulic bladder 170 could have its internal volume adjustable, as in the earlier embodiments, so that the overall support could be adjusted for each individual user.

It should also be understood that this form of the support block 144 could be used by itself, as with blocks 44 and 86. Also, block 144 could be provided, in that case, with a tether similar to tether 66.



As shown in Fig. 9 the support assembly 130 could also include a larger fluid bladder 162 that would be similar to bladder 48 shown in Fig. 1. Consequently, further discussion of that bladder, and its utility in the support system of the present invention, is not required here.

While the invention has been described in connection with what are presently considered to be the most practical and preferred embodiments, it is to be understood that the invention is not to be limited to the disclosed embodiments, but on the contrary, is intended to cover various modifications and equivalent arrangements included within the spirit and scope of the appended claims.

WHAT IS CLAIMED IS:

1. A spinal support device for applying  
specific support pressure to the sacral portion  
5 of the spine comprising a rigid support member  
having at least top, opposing side and front  
surfaces and a brace member to which said rigid  
support member is attached.

10 2. A support device as in claim 1 further  
including a padding member positioned so as to  
extend across at least a portion of said front  
surface.

15 3. A support device as in claim 1 wherein  
said padding member is comprised of foam.

20 4. A support device as in claim 1 wherein  
said padding member is comprised of a hollow  
bladder.

5. A support device as in claim 1 wherein  
said padding member is a fluid filled chamber.

25 6. A support device as in claim 1 wherein  
said brace member includes an upstanding portion

attached to said rigid support and a seat  
engaging portion.

5 7. A support device as in claim 6 wherein  
said seat engaging portion is flexible.

8. A support device as in claim 6 wherein  
said rigid support, said padding member and said  
retainer member are integrally formed.

0 9. A support device as in claim 1 wherein  
said rigid support further includes an anatomical  
conforming front surface.

5 10. A support device as in claim 9 wherein  
said anatomical conforming front surface  
comprises a foam layer.

0 11. A support device as in claim 9 wherein  
said anatomical conforming front surface  
comprises a fluid filled chamber.

5 12. A support device as in claim 11 wherein  
said fluid has a viscosity ranging from about  
0.01 to about 10,000 centipoise at 20°C.

13. A sacral support for use with a seat having back and bottom portions directing and concentrating force anteriorly on the posterior of the sacrum comprising a rigid member having seat contacting rear and bottom surfaces and a shaped anterior surface that extends from a position substantially level with the sacral base line to the surface of the bottom seat portion and horizontally a distance of about twice the posterior portion of the sacrum adjacent the sacral base line.

14. A sacral support as in claim 13 wherein the rigid member has a top portion that has a greater width dimension than a bottom portion thereof.

15. A sacral support as in claim 14 wherein the rigid member has a top to bottom width ratio of about 2.5:1.

16. A sacral support as in claim 14 wherein the rigid member has a top to bottom thickness ratio of about 1:2.

17. A sacral support as in claim 13 wherein said rigid member further includes a bulbous

portion extending anteriorly from a lower portion of the anterior surface.

5 18. A sacral support as in claim 14 wherein said rigid member further includes a bulbous portion extending anteriorly from a lower portion of the anterior surface.

0 19. A sacral support as in claim 13 wherein said rigid member further includes padding extending across said anterior surface.

5 20. A sacral support as in claim 19 wherein said padding comprises a fabric material.

21. A sacral support as in claim 19 wherein said padding comprises a foam material.

0 22. A sacral support as in claim 19 wherein said padding comprises a fluid filled bladder.

23. A sacral support as in claim 22 wherein the fluid comprises air.

5 24. A sacral support as in claim 22 wherein the fluid comprises a liquid having a viscosity ranging from 0.01 to 10,000 centipoise at 20°C.

25. A sacral support as in claim 13 further including a support member having an upstanding portion connection to said rigid member and a generally rearwardly extending portion.

5

26. A sacral support as in claim 25 wherein at least said severally rearwardly extending portion is flexible.

10

27. A sacral support device for exerting isolatable pressure on a designated spinal area comprising a rigid support member having at least top, opposing sides and front surfaces, said front surface having an anatomically  
15 accommodating curvature and an inflatable member extending at least partially about said top and opposing side surfaces and a seat accommodating frame member to which said rigid support member is attached.

20

28. A spinal support device comprised of a rigid block having top, bottom, opposing side, front and rear surfaces, said top having a width dimension that is wider than the width of said  
25 bottom, said front surface having a concave top to bottom extending curvature.

29. A lower back support mechanism for use with a seat having interconnected back and bottom portions comprising:

a rigid support member having a generally concave front surface having upper and lower sections, said lower section extending anteriorly of the upper section;

said support member further including a seat locating member extending therefrom so that when said locating member is positioned between the back and bottom portions said support member can be positioned on the seat relative to a user of the seat and relative to the back and bottom portions to produce localized pressure on the sacrum of the seat user.

30. A lower back support mechanism as in claim 29 wherein said seat locating member is flexible.

31. A lower back support mechanism as in claim 29 wherein said seat locating member is formed as an integral part of said support member.

32. A lower back support mechanism as in claim 29 wherein

said support member and said locating member are molded as an integral unit.

5           33. A lower back support mechanism as in claim 29 wherein said support member further includes a hydraulic bladder and a padded member each being secured onto the front concave surface.

10           34. A lower back support mechanism as in claim 33 wherein said hydraulic bladder is secured onto the upper section and the padded member is secured onto the lower section.


15           35. A lower back support mechanism as in claim 34 wherein said upper section comprises the upper one third of the front surface.

20           36. A method of supporting the neuro-musculo-skeletal system to produce pelvic stability in a seated position comprising the steps of placing a rigid support member at the juncture of a back and bottom portion of a seat, and positioning the rigid support member relative  
25           to an individual in the seat so that force is applied by the rigid support member against the sacrum of the individual.



5 37. A method of supporting the neuro-musculo-skeletal system as in claim 36 further including the step of placing a fluid bladder around upper and side margins of the support member, and inflating the fluid bladder so that an area surrounding the sacrum is supported in conjunction with the sacrum.

0 38. A method of supporting the neuro-musculo-skeletal system as in claim 36 wherein the rigid support member produces greater force against the sacral base portion of the sacrum.






FIG. 2





FIG. 3

FIG. 4



4/8




FIG. 5








FIG. 7

7 / 8





8 / 8




FIG. 10





FIG. 11

FIG. 12



# INTERNATIONAL SEARCH REPORT

International application No.

PCT/US95/09681

## A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) :A61G 15/00

US CL :128/845

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 128/845, 846, DIG. 23; 297/284; 602/5, 13, 19

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched  
NONE

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)  
NONE

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X --- Y	US, A, 1,667,626 (M. EPATEIN) 24 April 1928, see the entire document.	1-3, 6-10, 13, 14, 17-19, 21, 25, 26, 36 ----- 4, 5, 11, 12, 15, 16, 20, 22-24, 27-35, 37, 38
Y	US, A, 4,789,202 (ALTER) 06 December 1988, see the entire document.	4, 5, 11, 12, 15, 16, 20, 22-24, 27

☒ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

* Special categories of cited documents:	* T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
* A document defining the general state of the art which is not considered to be part of particular relevance	* X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
* E earlier document published on or after the international filing date	* Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
* L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	* A document member of the same patent family
* O document referring to an oral disclosure, use, exhibition or other means	
* P document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

27 SEPTEMBER 1995

Date of mailing of the international search report

13 OCT 1995

Name and mailing address of the ISA/US  
Commissioner of Patents and Trademarks  
Box PCT  
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

MICHAEL A. BROWN

Telephone No. (703) 308-2682

# INTERNATIONAL SEARCH REPORT

International application No.

PCT/US95/09681

## C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US, A, 3,348,880 (D. T. SWANN) 24 October 1967, see the entire document.	28-35, 37, 38